

MAGLOCKS

UL Listed Delayed Egress Kit



OPEN UP NEW HORIZONS
A HALMA COMPANY



Back of Maglock with LED display



Front of Maglock

ALL-IN-ONE KIT
EASY INSTALLATION
AFFORDABLE PROTECTION

Innovation
Quality
Service

BEA's Delayed Egress Kit is a simple to use, affordable, intelligent and code compliant solution.

- Built-in "sensor" detects when pressure is applied to outward swinging doors – No need to replace existing door hardware
- Field selectable to meet a variety of building codes
- Auto sensing voltage from 12–24 VDC and up to 1200lbs holding force
- Includes keyswitch for reset / override and an external sounder
- Unique highly visible "Red/Green" light panel indicates status of door
- Built-in Security Condition Sensor (SCS) feature indicates that the door is closed and bonded
- Provision for IBC, SBC, NFPA101, UBC, BOCA, or NBC of Canada compliance
- For single outswinging perimeter doors

WWW.BEASENSORS.COM



TECHNICAL SPECS

Housing Dimensions (LxWxH)
10 13/16" x 2 1/8" x 2 7/8"
(275mm x 54mm x 73mm)

Armature Dimensions (LxWxH)
7 7/16" x 5/8" x 2 3/8"
(189mm x 16mm x 60mm)

Voltage / Tolerance
12-24 VDC; ±10%

Max. Power / Current Draw
Maglock & Sounder:
0.61 A / 12VDC
0.32 A / 24VDC

Holding Force
Up to 1200 lbs

Certifications
UL / CUL Listed GWXT
Auxiliary Locks
UR / CUR Listed FWAX
Special Locking Arrangements

Operating Temperature
14° to 140° F
(-10° to +60° C)

Note: NOT FOR OUTDOOR USE

COMPONENTS



- 1 Front of Maglock
- 2 Back of Maglock with LED indicator
- 3 On / Off Keyswitch*
- 4 External Sounder
- 5 Alarm Signage

*Note: (Mortise Cylinder NOT Included with keyswitch)

HIGHLIGHTS

- ▶ All-in-One Delayed Egress locking system for applications requiring Loss Prevention, Life Safety and Traffic Control.
- ▶ Installation is simple by eliminating the need to replace existing door hardware.
- ▶ Dry contact relay switching (SPDT and DPDT) provided for local and / or remote alarm monitoring.
- ▶ Nuisance delay feature accomodates accidental triggering.
- ▶ MOV surge protection / Low voltage detection
- ▶ Brushed Anodized Aluminum finish (Maglock and Keyswitch)
- ▶ Keyswitch features RESET and OVER RIDE switch

APPLICATIONS & ACCESSORIES




Healthcare



Retail / Wholesale



Airports



Public Transit




Government




Museums / Galleries



Spacer Brackets



L / Z / U Brackets



Filler Bars



Power Supplies

RELATED PRODUCTS



Fly Kits
PIR detector for Request to Exit applications -
Includes: Sensor, Ceiling, and Surface Adapters



Power Supply
12 or 24 VDC with a battery backup option available



Push Buttons
Access Control push solution for any indoor application



Br3
Programmable 3 Relay logic module with 12 selectable functions



MS08U
Touchless Push Plate utilizing microwave motion technology